



Schedule 40 Schedule 160 Schedule 80 Seamless Carbon Steel Pipe For High-Temperature Service

Our Product Introduction

for more products please visit us on seamless-steeltube.com

Basic Information



Product Specification

- Application: Fluid Pipe, Structure Pipe, Boiler Pipe, Oil Pipe, Gas Pipe
- Name: Cold Rolled Seamless Steel Pipe
- Marking: According To Customer's Requirement
- Material: Carbon Steel, Stainless Steel, Alloy Steel, Etc
- Size: OD: 10-1000mm; WT: 1-100mm
- Length: 1-12m Or Customization
- Standard: ASTM A106/A53/API 5L Gr.B
- Surface Treatment: Black Painting, Anti-corrosion Coating
- Technique: Cold Rolled
- Package: In Bundles Or As Your Requirement
- Highlight: **schedule 160 seamless steel pipe, schedule 40 seamless steel pipe, seamless carbon steel pipe for high-temperature**



Product Description

Cold Rolled Seamless Steel Pipe With Anti Corrosion Coating

Seamless steel pipe with hollow section, a large number of used for conveying fluid pipeline, such as conveying oil, natural gas, gas, water and some solid material pipeline. Compared to the steel pipe and round steel solid steel bending torsional strength phase at the same time, the weight is lighter, is a kind of economic cross section steel.

Specifications

| | | | | | | | | | | | |
|---|---|-------|--|--------|--|-------|---|--------|---|--|---------------------|
| P r o d u c t | Seamless Steel Pipe | | | | | | | | | | |
| S e a m l e s s P i p e | <table> <tr> <td>China</td><td>GB/T8162/T8163 GB5310/6579/9948</td></tr> <tr> <td>U.S.A.</td><td>ASTM A53/A106/A178/A179/A192/A210/A213/A333/A335/A283/A135/A214/315/A500/A501/A519/A161/A334; API 5L/5CT</td></tr> <tr> <td>Japan</td><td>JIS G3452/G3454/G3456/G3457/G3458/G3460/3461/3462/3464</td></tr> <tr> <td>German</td><td>DIN 1626/17175/1629-4/2448/2391/17200 SEW680</td></tr> <tr> <td></td><td>GOST 8732/8731/3183</td></tr> </table> | China | GB/T8162/T8163 GB5310/6579/9948 | U.S.A. | ASTM A53/A106/A178/A179/A192/A210/A213/A333/A335/A283/A135/A214/315/A500/A501/A519/A161/A334; API 5L/5CT | Japan | JIS G3452/G3454/G3456/G3457/G3458/G3460/3461/3462/3464 | German | DIN 1626/17175/1629-4/2448/2391/17200 SEW680 | | GOST 8732/8731/3183 |
| China | GB/T8162/T8163 GB5310/6579/9948 | | | | | | | | | | |
| U.S.A. | ASTM A53/A106/A178/A179/A192/A210/A213/A333/A335/A283/A135/A214/315/A500/A501/A519/A161/A334; API 5L/5CT | | | | | | | | | | |
| Japan | JIS G3452/G3454/G3456/G3457/G3458/G3460/3461/3462/3464 | | | | | | | | | | |
| German | DIN 1626/17175/1629-4/2448/2391/17200 SEW680 | | | | | | | | | | |
| | GOST 8732/8731/3183 | | | | | | | | | | |
| M a t e r i a l | <table> <tr> <td>China</td><td>10#, 20#, 16Mn, 20G, 15MoG, 15CrMo, 30CrMo, 42CrMo, 27SiMn, 20CrMo</td></tr> <tr> <td>U.S.A.</td><td>Gr. B/Gr.A/A179/A192/A-1/T11/T12/T22/P1/FP1/T5/4140/4130</td></tr> <tr> <td>Japan</td><td>STPG38, STB30, STS38, STB33, STB42, STS49, STBA23, STPA25, STPA23</td></tr> <tr> <td>German</td><td>ST33, ST37, ST35, ST35.8, ST45, ST52, 15Mo3, 13CrMo44, 1.0309, 1.0305, 1.0405</td></tr> </table> | China | 10#, 20#, 16Mn, 20G, 15MoG, 15CrMo, 30CrMo, 42CrMo, 27SiMn, 20CrMo | U.S.A. | Gr. B/Gr.A/A179/A192/A-1/T11/T12/T22/P1/FP1/T5/4140/4130 | Japan | STPG38, STB30, STS38, STB33, STB42, STS49, STBA23, STPA25, STPA23 | German | ST33, ST37, ST35, ST35.8, ST45, ST52, 15Mo3, 13CrMo44, 1.0309, 1.0305, 1.0405 | | |
| China | 10#, 20#, 16Mn, 20G, 15MoG, 15CrMo, 30CrMo, 42CrMo, 27SiMn, 20CrMo | | | | | | | | | | |
| U.S.A. | Gr. B/Gr.A/A179/A192/A-1/T11/T12/T22/P1/FP1/T5/4140/4130 | | | | | | | | | | |
| Japan | STPG38, STB30, STS38, STB33, STB42, STS49, STBA23, STPA25, STPA23 | | | | | | | | | | |
| German | ST33, ST37, ST35, ST35.8, ST45, ST52, 15Mo3, 13CrMo44, 1.0309, 1.0305, 1.0405 | | | | | | | | | | |
| a n d G r a d e | 0, 20, 35, 45, 20X | | | | | | | | | | |
| O u t D i a m e t e r | 10-1000mm or customization | | | | | | | | | | |
| W a l l T h i c k n e s s | 1-100mm or customization | | | | | | | | | | |
| L e n g t h | 1-12m or customization | | | | | | | | | | |
| P r o t e c t i o n | Plastic caps | | | | | | | | | | |
| P a c k i n g t e r m s | Labeled and bundled together with steel strip | | | | | | | | | | |

| | |
|--|---|
| S h i p m e n t e r m s | Containers or bundles by sea,one 20" container can load about 20 tons(5.8meters long),one 40" container can load about 23-25tons(less than 11.8meters long) |
| Q u a l i t y C e r t i f i c a t e | ISO, API, Mill Test Certificate |

Our Advantages

1. Reasonable price with excellent quality
2. Abundant stock and prompt delivery
3. Rich supply and export experience, sincere service
4. Reliable forwarder

Application

1. Fence, greenhouse, door pipe, greenhouse
2. Low pressure liquid, water, gas, oil, line pipe
3. For both indoor and outdoor the building construction
4. Widely used in scaffolding construction which is much cheaper and convenient



Q1. Are you a manufacturer or trader?

We are a manufacturer, and we can have our own factory produced many steel products.

Q2. Whether your company supports Trade Assurance order?

Yes, we can (100% product quality protection; 100% on-time shipment protection; 100% payment protection)

Q3. Can we get the some samples? Any charges?

Yes, you can get available samples in our stock. If the samples from new production, we will charge some reasonable cost, but this amount will be deducted from your first order.

Q4. How do we build up business relations with your company?

Send us your requirement which includes size, coating info, parameters, quantity, destination .

Q5. What is the MOQ?

We can accept small orders. Please feel free to contact us, we can meet your requirements.

Q6. What's your advantage?

With high-quality products and efficient customer service, we adhere to the principle of customer first.

Q7. How long is your delivery time?

Delivered within 15 days after receipt of deposit.



Shandong Fengbao Metal Products Co., Ltd



13003369243



Lydia@fengbaosteels.com



seamless-steeltube.com